



Engineering Data Sheet: 2224

Unit Information

Model #: 2224 / Item # 14720
UPC-IC (12 Digit): 01673147204

Master Pack Dimensions

Weight: 5.8 lbs. (2.6 kg)
Cube: 0.48 ft³ (0.014 m³)
Quantity: 12

Specifications

Power Source : Carbon Zinc Only: 3xD-cell
Bulb/Lamp: PR-3
Bulb/Lamp Life: 15 Hours
Light Output: 15,000 Beam Candlepower
770 Candelas Peak Beam Intensity
Weight (Without batteries): 6.0 oz (.17 kg)

Components

Lens Ring: Polypropylene (Black)
Lens: Unbreakable Tuflexx®
Reflector: ABS
Tube: Polypropylene (Safety Orange)
Contact Strip: Spring brass & tin steel
Switch: Polypropylene
Bottom Cap: Polypropylene (Black)

Product Features

- For use in hazardous atmospheres
- Division 1 UL & CUL approved
- Waterproof
- Three-way switch : On-Off-Flash
- Anti-roll tube
- Oversized, faceted reflector for more light
- Circuit breaking mechanism

Accessories

<u>Accessories</u>	<u>Description</u>
23853	6 ½" Red Snap In Wand
23860	6 ½" Yellow Snap In Wand
20332	PR3 Bulb

Unit Dimensions

Length: 10.2 in. (25.1 cm)
Width: 2.3 in. (5.8 cm) at head
Height: N/A

Safety Approvals

UL/CUL: Class I, Div 1, Group C & D
Class II, Div 1, Group G

ASTM & MSHA: Approved



WorkSafe™ I Model
#2224

