55 Natural Rubber Latex HD™



Unsupported Natural latex coating

DESCRIPTION

- · Fully coated
- Rolled cuff
- · Standard finish
- Without special treatment
- · Available by individual pair in polybag with eyelet
- · Wear indicator overdip



BENEFITS

- A thin, light glove with a "second skin" feel
- · Protects the hand from water, chemicals and abrasion while remaining elastic and breathable
- Impermeable for working in damp or greasy environments
- · Cuff prevents dirt from entering the glove
- · Lower allergy risks
- · Packaging that helps finding the right model in displays
- · Blue color spotted when the coating is damaged
- · Wrist well protected
- · Low-soil colour

RECO	MMENI	DED E	OR T	HESE	RISK	G.

Chemicals

Abrasion

Slips

RECOMMENDED FOR THESE LINES OF **WORK:**

Chemical industry / Acid components Chemical industry / Solvents

AVAILABLE SIZES 9/L • 10/XL • 11/XXL **LENGTH** 380 Dependent on size, in mm (flat) **PACKAGING** Pairs or pieces per pack/box 1/12/36 **COLOUR OF SUPPORT/COATING Black**

RECOMMENDATIONS FOR USE

- · Store away from light and humidity
- Potential allergents: carbamate and natural rubber latex
- · Rinse the gloves in running water before removing, using a neutral detergent if
- · Do not wear gloves when there is a risk of entanglement by moving parts of machines.



Globus Building 38 Wheel Forge Way Trafford Park, Manchester M17 1EH

Tel: 0161 877 4747 Fax: 0161 877 4746 www.globus.co.uk



ABRASION CUTTING 0 1 2 3 4 0 1 2 3 4 5 TEARING PUNCTURE

0 <u>1</u> 2 3 4 5







HYDROCHLORIC ACID 36% KEROSENE <u>0</u>123456

METHANOL

CAUSTIC SODA 4% <u>0</u>123456







EC compliance certificate delivered by the notified body 0516 STFI Germany - Postfach 1325 - D-09072 Chemnitz - Germany

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.